

Tow Like A Champion!

TOUGH. Designed specifically for use as a towing device. Manufactured from monofilament polypropylene. This unique product withstands contact with fuels, fertilizers and various other chemicals as well as being water resistant.

SAFE. Designed to stretch from 12 to 15 percent. This is enough to absorb the normal shock of pulling and towing, while greatly reducing recoil.

VERSATILE.

Loop/Loop ropes consist of a loop being braided back into each end of the rope.



Loop/Sling ropes have a regular loop on one end and an oversized loop (sling) on the other end that is large enough to feed the rope back through. This loop/sling combination greatly increases hook up options.



Loop/Ring ropes have a loop on one end and a Heavy Duty Oval Master Ring on the other end.



Ring/Ring ropes consist of a Heavy Duty Oval Master Ring installed in each end of the rope which helps extend the life of the rope and increase ease of hook up.



"We quit using chains and other tow ropes years ago. What we really liked about our **Champion Tow Rope** is that there is enough stretch to get the energy that we need without the recoil potential that we've seen in other ropes."

Tow Like A Champion!



A Division Of

BAKKO
Industries, Inc.

28958 198th Avenue
Glenwood, MN 56334

800-584-6675 (toll-free)
www.bakkoindustries.com



Tough. Safe. Versatile.



**The Ultimate in Convenience,
Safety, and Ease of Hook Up**

Rope Sizes & Part Numbers

Rope #	Diameter	Length	Tensile Strength	Black	Green	Cordura Sleeve	Clevis	Ring	Use
1220LL	1"	20 ft	12,000#	38112	37112	38011	-	-	ATVs, Cars
2520LL	1 1/2"	20 ft	25,000#	38211	37211	38012	38978	38985	2 & 4 Wheel Drive Pickups, Tractors Up to 75 HP
2520LS	1 1/2"	20 ft	25,000#	38825	37825	38012	38978	38985	
5025LL	2"	25 ft	50,000#	38311	37311	38013	38901	38986	Trucks, Tractors Up to 150 HP
5025LS	2"	25 ft	50,000#	38850	37850	38013	38901	38986	
7515LL	2 1/2"	15 ft	75,000#	38451	37451	38017	38918	38983	Semis, Tractors Up to 275 HP
7525LL	2 1/2"	25 ft	75,000#	38454	37454	38024	38918	38983	
7530LL	2 1/2"	30 ft	75,000#	38411	37411	38014	38918	38983	
7530LS	2 1/2"	30 ft	75,000#	38875	37875	38014	38918	38983	
10015LL	3"	15 ft	100,000#	38551	37551	38018	38914	38983	Construction, Oil Field Eq., Tractors Up to 375 HP
10025LL	3"	25 ft	100,000#	38554	37554	38025	38914	38983	
10035LL	3"	35 ft	100,000#	38511	37511	38015	38914	38983	
10035LS	3"	35 ft	100,000#	38800	37800	38015	38914	38983	
12515LL	3 1/4"	15 ft	125,000#	38651	37651	38019	38913	38983	Tiling, Construction, Tractors Up to 475 HP
12525LL	3 1/4"	25 ft	125,000#	38654	37654	38026	38913	38983	
12540LL	3 1/4"	40 ft	125,000#	38611	37611	38016	38913	38983	
12540LS	3 1/4"	40 ft	125,000#	38812	37812	38016	38913	38983	
15015LL	3 1/2"	15 ft	150,000#	38751	37751	38020	38912	38984	Tiling, Construction, Tractors Up to 550 HP
15025LL	3 1/2"	25 ft	150,000#	38754	37754	38027	38912	38984	
15045LL	3 1/2"	45 ft	150,000#	38711	37711	38021	38912	38984	
15045LS	3 1/2"	45 ft	150,000#	38815	37815	38021	38912	38984	
20015LL	4"	15 ft	200,000#	38251	37251	38022	38934	38984	Extra Large Equipment, Quad Tractors Up to 625 HP
20025LL	4"	25 ft	200,000#	38254	37254	38028	38934	38984	
20050LL	4"	50 ft	200,000#	38201	37201	38023	38934	38984	
20050LS	4"	50 ft	200,000#	38202	37202	38023	38934	38984	

LL = Loop/Loop
LS = Loop/Sling

Add Ring(s) for
Loop/Ring & Ring/Ring

Cordura Sleeves are Recommended
if Excessive "Dragging" is Expected

Ropes Will Not Absorb Water and
Will Remain Flexible in Cold Weather

For Warranty and Repair Info,
Visit www.bakkoindustries.com

